

CHECKLISTE PITCHED



Customer name

Project address

Project name

Roof section

Roof covering

Tiled Roof

☐ Concrete tile	Rafter spacing		mm
☐ Beaver tile	Rafter dimension		mm
☐ Slate tile	Batten dimensions		mm
☐ no tile / In-roof	Height of insulation above rafters		mm

Metal roof

☐ Trapezoidal sheet	Seam / joint / corrugation spacing		mm
☐ Sanding seam	Sheet thickness		mm
☐ Corrugated sheet	☐ Aluminum ☐ Steel ☐ Copper ☐ Titanium zinc		

Other coverings

☐ Corrugated fiber cement	☐ Rafter ☐ Purlin	☐ Wood ☐ Metal
☐ Sandwich	Rafter or purlin spacing	mm
☐ Foil	Rafter or purlin spacing	mm
☐ Bitumen		

Roof Dimensions

Ridge height		mm	Slope		Degree
Width		mm	Orientation		Degree
Length		mm			

PV-Modul

Length		mm	Weight		kg
Width		mm	Power		Wp
Thickness		mm	Manufacture		

Zusatzinformationen

☐ Roof to be maximally covered	☐ Black components
☐ Target project size kWp	☐ Equipotential bonding
☐ Offer incl. freight to project address	☐ Integration into lightning protection system